



### EUROCEL 704

#### Short description:

Removable double sided adhesive tape

#### Product Data

<b>Backing:</b>	0.050 mm yellow PP cast
<b>Adhesive:</b>	Outer side: acrylic Inner side : synthetic rubber
<b>Liner:</b>	double sided white siliconized paper
<b>Total thickness (without liner)</b>	0.150 mm
<b>Adhesion to steel</b>	o.s. 3.7 N/25mm c.s. 37 N/25mm
<b>Tensile strength MD</b>	50 N/25mm
<b>Elongation at break</b>	600 %
<b>Temp. Resistance</b>	60 °C

#### Application

Floor removable double sided tape, recommended for holding exhibitions and promotion events, temporary applications in household use when carpets , runners, etc, floor holding are required.  
*The removable side of the tape is the outer: first apply the tape to the floor, then remove the liner and apply the carpet. Please always test on any surface involved.*  
*After application removal is suggested within 15 days.*

Features	Benefits
Synthetic rubber ( <i>inner side</i> )	<ul style="list-style-type: none"> <li>➤ High adhesion on all carpets, runners, etc.</li> <li>➤ Safe holding</li> </ul>
Acrylic adhesive ( <i>outer side</i> )	<ul style="list-style-type: none"> <li>➤ High performance on several surfaces</li> <li>➤ Easily removable without adhesive transfer</li> </ul>
Yellow PP cast backing	<ul style="list-style-type: none"> <li>➤ Highly conformable</li> <li>➤ Position highlight thanks to the yellow colour</li> <li>➤ Hand tearable</li> <li>➤ Removable without breaking</li> </ul>

*Product shelf life and storage: 12 months, based on the product being stored at 23°C/50% relative humidity out of direct sunlight.*

SICAD S.p.A., Via Caduti della Liberazione, 57 21040 Uboldo (VA) - ITALY  
 Tel.+39 02 96412.1; Fax +39 02 96412322 export market; Fax +39 02 96780832 domestic market;  
 E-mail: info@eurocel.it - www.eurocel.it - www.sicadgroup.com

This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss